

THE APPLICATION OF DCP MIDSTREAM, LP TO CONSTRUCT AND OPERATE A HYDROGEN SULFIDE GAS GATHERING PIPELINE, FULLERTON 12" SOUTH LOOP, ANDREWS COUNTY, TEXAS

REVIEWED BY: Richard D. Atkins, P.E. - Technical Examiner

DATE APPLICATION FILED: October 15, 2010

DATE REVIEWED: December 20, 2010

EXAMINER'S REPORT AND RECOMMENDATION

STATEMENT OF THE CASE

DCP Midstream, LP ("DCP") requests Commission authority pursuant to Statewide Rules 106, 70 and 36, to construct and operate a hydrogen sulfide (H₂S) gas gathering pipeline in Andrews County, Texas. The proposed sour gas pipeline will transport gas from an existing sour gas pipeline located south of the Fullerton Field to the DCP Fullerton Gas Plant Site.

The Commission's Field Operations section has reviewed the application and has determined that the application complies with the applicable provisions of Statewide Rule 36. In addition, the Commission's Safety Division and Gas Services Division have reviewed the application and recommend approval. The examiner has also reviewed the application and recommends approval.

DISCUSSION OF THE EVIDENCE

DCP proposes construction of a high pressure sour gas gathering pipeline which will transport gas from an existing sour gas pipeline located south of the Fullerton Field to the DCP Fullerton Gas Plant Site. The line will be 12 inches in diameter and will be approximately 9.5 miles in length. The line is located approximately 15 miles west of Andrews, Texas, and crosses Texas State Highway 176.

The calculated 100 ppm radius of exposure is 5,577 feet and the calculated 500 ppm radius of exposure is 2,548 feet. These calculations are based on a H₂S concentration of 10,520 ppm and a maximum escape volume of 58 MMCFGPD. The maximum operating pressure is 1,440 psi. The pipeline is located in a rural non-populated area of Andrews County. The 500 ppm radius of exposure will encompass portions of Texas State Highway 176, FM 1967 and FM 181. The 100 ppm radius of exposure will encompass an Exxon Mobil field office (See Attached ROE Map). The applicant has

submitted a contingency plan in accordance with the provisions of Rule 36(c)(9).

To comply with Statewide Rule 36(c)(8), DCP will use safety control and automatic devices. The line will be protected by high and low pressure sensors that will activate an Emergency Shutdown Valve (ESDV). If the monitors sense a high or low pressure condition, 850 psi and 350 psi respectively, then the pipeline will be shut-in by the ESDV, which will trigger an alarm at the DCP Fullerton Gas Plant. The pipeline will be monitored 24/7.

All materials will satisfy the requirements described in the latest edition of the NACE Standard MR0175-2003. The pipe will be API 5L-X42 grade steel pipe and all welds will be x-rayed. H₂S warning signs compliant with Rule 36(c)(6)(A) and (c)(6)(B) will be posted at all public road crossings as well as intervals along the pipeline frequent enough as to provide warning to avoid accidental rupture of the line by excavation. The signs will indicate poison gas, company name and emergency phone numbers. The line will be buried a minimum of 4 feet below ground level.

DCP published notice of the application in a newspaper of general circulation in Andrews County. The notice was published in the *Andrews County News* on November 7, 2010. The application was filed with the Andrews County Clerk on November 2, 2010.

FINDINGS OF FACT

1. On October 15, 2010, DCP Midstream, LP filed an application for a permit to construct a hydrogen sulfide gas gathering pipeline in Andrews County.
2. DCP published notice of the application in a newspaper of general circulation in Andrews County. The notice was published in the *Andrews County News* on November 7, 2010. The application was filed with the Andrews County Clerk on November 2, 2010.
3. No protest to the application was filed with the Commission and no hearing was held.
4. DCP proposes construction of a H₂S gas gathering pipeline in Andrews County approximately 15 miles west of Andrews, Texas.
 - a. The 12 inch pipeline will transport gas from an existing sour gas pipeline located south of the Fullerton Field to the DCP Fullerton Gas Plant Site.
 - b. The line will be approximately 9.5 miles in length.
5. Pipeline materials and construction will meet the NACE standards as required by Statewide Rule 36 for hydrogen sulfide service.

6. The line will be operated at a maximum pressure of 1,440 psig.
7. The maximum volume delivery design is 58 MMCFGPD. The hydrogen sulfide concentration of the gas to be transported is 10,520 parts per million.
8. The calculated 100 ppm radius of exposure is 5,577 feet and the calculated 500 ppm radius of exposure is 2,548 feet.
 - a. The 500 ppm radius of exposure will encompass portions of Texas State Highway 176, FM 1967 and FM 181.
 - b. The 100 ppm radius of exposure will encompass an Exxon Mobil field office.
9. Applicant submitted a contingency plan in accordance with the provisions of Rule 36(c)(9).
10. The pipeline will be constructed subject to Commission inspections for compliance with the appropriate Commission Rules.
11. The Commission's Deputy Director of Field Operations and the Commission's Gas Services Division have reviewed the application and recommend approval.

CONCLUSIONS OF LAW

1. Proper notice was timely given to all parties entitled to notice pursuant to applicable statutes and rules.
2. All things have occurred and have been accomplished to give the Commission jurisdiction in this case.
3. The application complies with Statewide Rules 36, 70 and 106.
4. Approving the application for a permit to construct and operate the proposed gas pipeline is consistent with the rules and safety standards adopted by the Commission.

EXAMINER'S RECOMMENDATION

The examiner recommends that the application of DCP Midstream, LP to construct and operate the proposed H₂S gas gathering pipeline be approved as set out in the attached Final Order.

Respectfully submitted,

Richard D. Atkins, P.E.
Technical Examiner