RAILROAD COMMISSION OF TEXAS OFFICE OF GENERAL COUNSEL

OIL AND GAS DOCKET NO. 08-0247565 IN THE WAHA (CHERRY CANYON-H2S DISP) FIELD, PECOS COUNTY, TEXAS

FINAL ORDER

APPROVING THE APPLICATION OF REGENCY GAS SERVICES WAHA, LP FOR INJECTION OF FLUIDS CONTAINING HYDROGEN SULFIDE INTO A POROUS FORMATION NOT PRODUCTIVE OF OIL OR GAS IN ITS WAHA PLANT LEASE WELL NO. 1
WAHA (CHERRY CANYON-H2S DISP) FIELD PECOS COUNTY, TEXAS

The Commission finds that after statutory notice in the above-numbered docket heard on June 30, 2006, the presiding examiner has made and filed a report and recommendation containing findings of fact and conclusions of law, for which service was not required; that the proposed application is in compliance with all statutory requirements; and that this proceeding was duly submitted to the Railroad Commission of Texas at conference held in its offices in Austin, Texas.

The Commission, after review and due consideration of the examiner's report and recommendation, the findings of fact and conclusions of law contained therein, hereby adopts as its own the findings of fact and conclusions of law contained therein, and incorporates said findings of fact and conclusions of law as if fully set out and separately stated herein.

Therefore, it is **ORDERED** by the Railroad Commission of Texas that a New Field Designation to be known as the Waha (Cherry Canyon-H2S Disp) Field (No. 94648 100), Pecos County, Texas, be and it is hereby approved.

It is further **ORDERED** by the Railroad Commission of Texas that Regency Gas Services Waha, LP be and is hereby authorized to dispose of fluids containing hydrogen sulfide into its Waha Plant Lease Well No. 1, as specified in the programs set out in detail in public hearing as provided in Section (C)(10) of Rule 36 of the Commission's Rules and Regulations of Statewide application, Waha (Cherry Canyon-H2S Disp) Field, Pecos County, Texas, subject to the following terms and conditions:

SPECIAL CONDITIONS:

- 1. Oil and gas waste shall only be injected into strata in the subsurface depth interval from <u>6170</u> feet to <u>6480</u> feet.
- 2. The injection volume shall not exceed <u>2000</u> barrels of acid gas per day.
- 3. The maximum operating surface injection pressure shall not exceed 2000 psig.
- 4. Before injection operations can begin, Regency Gas Services Waha, LP must have an approved contingency plan.
- 5. A permanent marker shall be placed on the wellhead of the Waha Plant Lease Well No. 1 after injection ceases to notify persons of possible high hydrogen sulfide content in this wellbore.

STANDARD CONDITIONS:

- 1. Injection must be through tubing set on a packer. The packer must be set no higher than 100 feet above the top of the permitted interval.
- 2. The District Office must be notified 48 hours prior to:
 - a. running tubing and setting packer;
 - b. beginning any workover or remedial operation;
 - c. conducting any required pressure tests or surveys.
- 3. The wellhead must be equipped with a pressure observation valve on the tubing and for each annulus.
- 4. Prior to beginning injection, and subsequently after any workover, an annulus pressure test must be performed. The test pressure must equal the maximum authorized injection pressure or 500 psig, whichever is less, but must be at least 200 psig. The test must be performed and the results submitted in accordance with the instructions of Form H-5.
- 5. The injection pressure and injection volume must be monitored at least monthly and reported annually on Form H-10 to the Commission's Austin Office.
- 6. Within 30 days after completion, conversion to disposal, or any workover which results in a change in well completion, a new Form W-2 or G-1 must be filed in duplicate with the District Office to show the current completion status of the well. The date of the disposal well permit and the permit number must be included on the new Form W-2 or G-1.
- 7. Written notice of intent to transfer the permit to another operator must be submitted to the Commission at least 15 days prior to the date the transfer will occur by filing Form P-4.
- 8. This permit will expire when the Form W-3, Plugging Record, is filed with the Commission.
- 9. Form P-18, Skim Oil Report, must be filed in duplicate with the District Office by the 15th day of the month following the month covered by the report.
- 10. That the well be identified and operated according to Permit Number_____.
- 11. Prior to beginning operation, all collecting pits, skimming pits, or washout pits must be permitted under the requirements of Statewide Rule 8.

Provided further that, should it be determined that such injection fluid is not confined to the approved strata, then the permission given herein is suspended and disposal operation must be stopped until the fluid migration from such strata is eliminated. The special permit conditions may be modified after notice and opportunity for hearing to prevent migration of injection fluid from the approved strata.

Done this eighth day of August, 2006.

RAILROAD COMMISSION OF TEXAS (Order approved and signatures affixed by OGC Unprotested Master Order dated August 8 2006.)