

**RAILROAD COMMISSION OF TEXAS
OFFICE OF GENERAL COUNSEL**

**OIL AND GAS DOCKET
NO. 10-0258437**

**IN THE WEST PARK (GRANITE
WASH) FIELD, HEMPHILL AND
WHEELER COUNTIES, TEXAS**

**FINAL ORDER
ADOPTING THE FIELD RULES
FOR THE WEST PARK (GRANITE WASH) FIELD
HEMPHILL AND WHEELER COUNTIES, TEXAS**

The Commission finds that after statutory notice in the above-numbered docket heard on September 5, 2008, the presiding examiner has made and filed a report and recommendation containing findings of fact and conclusions of law, for which service was not required; that the proposed application is in compliance with all statutory requirements; and that this proceeding was duly submitted to the Railroad Commission of Texas at conference held in its offices in Austin, Texas.

The Commission, after review and due consideration of the examiner's report and recommendation, the findings of fact and conclusions of law contained therein, hereby adopts as its own the findings of fact and conclusions of law contained therein, and incorporates said findings of fact and conclusions of law as if fully set out and separately stated herein.

Therefore, it is ordered by the Railroad Commission of Texas that the following field rules shall be adopted for the West Park (Granite Wash) Field, Hemphill and Wheeler Counties, Texas:

RULE 1: The entire correlative interval from 11,400 feet to 14,750 feet as shown on the log of the Zybach Well No. 1, API No. 483-31386, Section 2, Camp CSL, Lot 13, A-26, Wheeler County, Texas, shall be designated as a single reservoir for proration purposes and be designated as the West Park (Granite Wash) Field.

RULE 2: No well for oil or gas shall hereafter be drilled nearer than FOUR HUNDRED SIXTY-SEVEN (467) feet to any property line, lease line, or subdivision line and no well shall be drilled nearer than SIX HUNDRED SIXTY (660) feet to any applied for, permitted or completed well in the same reservoir on the same lease, pooled unit or unitized tract. The aforementioned distances in the above rule are minimum distances to allow an operator flexibility in locating a well, and the above spacing rule and the other rules to follow are for the purpose of permitting only one well to each drilling and proration unit in either field. Provided however, that the Commission will grant exceptions to permit drilling within shorter distances and drilling more wells than herein prescribed whenever the Commission shall have determined that such exceptions are necessary either to prevent waste or to prevent the confiscation of property. When exception to these rules is desired, application therefore shall be filed and will be acted upon in accordance with the provisions of Commission Statewide Rules 37 and 38, which applicable provisions of said rules are

incorporated herein by reference. The standard drilling unit shall remain FORTY (40) acres.

Provided, however, that for purposes of spacing for horizontal wells, the following shall apply:

- a. A take point in a horizontal drainhole well is any point along a horizontal drainhole where oil and/or gas can be produced into the wellbore from the reservoir/field interval. The first take point may be at a different location than the penetration point and the last take point may be at a location different than the terminus point.
- b. All take points in a horizontal drainhole well shall be a minimum of FOUR HUNDRED SIXTY SEVEN (467) feet from a property line, lease line, or subdivision line. A permit or an amended permit is required for all take points closer to the lease line than the lease line spacing distance, including any perforations added in the vertical portion or the curve of a horizontal drainhole well.
- c. All take points in a horizontal drainhole well shall be a minimum distance of SIX HUNDRED SIXTY (660) feet from any existing, permitted, or applied for vertical well on the same lease, unit or unitized tract and from take points in any existing, permitted, or applied for horizontal drainhole on the same lease, unit or unitized tract.

In addition to the penetration point and the terminus of the wellbore required to be identified on the drilling permit application (Form W-1H) and plat, all proposed take points must also be identified on the drilling permit application (remarks section) and plat. Operators shall file an as-drilled plat showing the path, penetration point, terminus and all take points of all drainholes in horizontal wells, regardless of allocation formula.

In applying this rule, the general order of the Commission with relation to the subdivision of property shall be observed.

Under the following conditions, an operator, at its option, shall be granted an exception to Statewide Rule 38 and permitted to form fractional units of less than FORTY (40) acres:

- (a) The Railroad Commission shall notify in writing the designated operators, lessees of record for tracts that have no designated operator, and all owners of unleased mineral interests (i) within 660 feet from the bottomhole location of a vertical well or (ii) within 660 feet of any take point on a horizontal well within the correlative interval.
- (b) Designated operators, lessees of record for tracts that have no designated operator, and all owners of unleased mineral interests receiving this written notification shall have 21 days from the date of issuance of the notice of application for a Rule 38 density exception to file a written protest with the Railroad Commission, such protest to be received by the Railroad Commission within said 21 day period.

- (c) If no written protest is received by the Railroad Commission within the 21 day period of time, or if written waivers are received from each designated operator, lessee of record for tracts that have no designated operator, and all owners of unleased mineral interests to whom notice is required, the application shall be approved administratively by the Railroad Commission.
- (d) If a written protest is received by the Railroad Commission within 21 days of the date of issuance of the notice of application, the application will be scheduled for hearing at which the applicant must show that the fractional proration unit and the well thereon are necessary to effectively drain an area of the field that will not be effectively drained by existing wells, or to prevent waste or confiscation.
- (e) Permits granted pursuant to the above provision shall be issued as exceptions to Statewide Rule 38.

Operators shall not be required to file Form P-15 or proration unit plats for any well in the field.

For the purpose of assigning additional acreage to a horizontal well pursuant to Rule 86, the distance from the first take point to the last take point in the horizontal drainhole shall be used in such determination, in lieu of the distance from penetration point to terminus.

RULE 3: For oil and gas wells, Stacked Lateral Wells within the correlative interval for the field that are drilled from different wellbores may be considered a single well for regulatory purposes, as provided below:

1. A horizontal drainhole well qualifies as a Stacked Lateral Well under the following conditions:
 - a) There are two or more horizontal drainhole wells on the same lease or pooled unit within the correlative interval for the field;
 - b) Horizontal drainholes are drilled from at least 2 different surface locations on the same lease or pooled unit;
 - c) There shall be no more than 250 feet between the surface locations of horizontal drainholes qualifying as a Stacked Lateral Well.
 - d) Each point of a Stacked Lateral Well's horizontal drainhole shall be no more than 300 feet in a horizontal direction from any point along any other horizontal drainhole of that same Stacked Lateral Well. This distance is measured perpendicular to the orientation of the horizontal drainhole and can be illustrated by the projection of each horizontal drainhole in the Stacked Lateral Well into a common horizontal plane as seen on a location plat; and
 - e) There shall be no maximum or minimum distance limitations between horizontal drainholes of a Stacked Lateral Well in a vertical direction.
2. A Stacked Lateral Well, including all surface locations and horizontal drainholes comprising such Stacked Lateral Well, shall be considered as a single well for density and allowable purposes.

3. Each surface location of a Stacked Lateral Well must be permitted separately and assigned an API number. In permitting a Stacked Lateral Well, the operator shall identify each surface location of such well with the designation "SL" in the well's lease name and also describe the well as a Stacked Lateral Well in the "Remarks" of the Form W-1 drilling permit application. The operator shall also identify on the plat any other existing, or applied for, horizontal drainholes comprising the Stacked Lateral Well being permitted.
4. To be a regular location, each horizontal drainhole of a Stacked Lateral Well must comply with (i) the field's minimum spacing distance as to any lease, pooled unit or property line, and (ii) the field's minimum between well spacing distance as to any different well, including all horizontal drainholes of any other Stacked Lateral Well, on the same lease or pooled unit in the field. Operators may seek exceptions to Rules 37 and 38 for Stacked Lateral Wells in accordance with the Commission's rules, or any applicable rule for this field.
5. Operators shall file separate completion forms for each surface location of the Stacked Lateral Well. Operators shall also file a certified as-drilled location plat for each surface location of a Stacked Lateral Well showing each horizontal drainhole from that surface location, confirming the well's qualification as a Stacked Lateral Well and showing the maximum distances in a horizontal direction between each horizontal drainhole of the Stacked Lateral Well.
6. In addition to the completion forms for each surface location of a Stacked Lateral Well, the operator must file a separate Form G-1 or Form W-2 for record purposes only for the Commission's Proration Department to build a fictitious "Record Well" for the Stacked Lateral Well. This Record Well will be identified with the words "SL Record" included in the lease name. This Record Well will be assigned an API number and Gas Well ID or Oil lease number and listed on the proration schedule with an allowable if applicable.
7. In addition to the Record Well, each surface location of a Stacked Lateral Well will be listed on the proration schedule, but no allowable shall be assigned for an individual surface location. Each surface location of a Stacked Lateral Well shall be required to have a separate G-10 or W-10 test and the sum of all horizontal drainhole test rates shall be reported as the test rate for the Record Well.
8. Operators shall report all production from horizontal drainholes included as a Stacked Lateral Well on Form PR to the Record Well. Production reported for a Record Well is the total production from the horizontal drainholes comprising the Stacked Lateral Well. Operators shall measure the production from each surface location of a Stacked Lateral Well. Operators may measure full well stream with the measurement adjusted for the allocation of condensate based on the gas to liquid ratio established by the most recent G-10 well test rate for that surface location. The gas and condensate production will be identified by individual API number and recorded and reported on the "Supplementary Attachment to Form PR".

9. If the field's 100% AOF status should be removed, the Commission's Proration Department shall assign a single gas allowable to each Record Well classified as a gas well. The Commission's Proration Department shall also assign a single oil allowable to each Record Well classified as an oil well. The assigned allowable may be produced from any one or all of the horizontal drainholes comprising the Stacked Lateral Well.

10. Operators shall file an individual Form W-3A Notice of Intention to Plug and Abandon and Form W-3 Well Plugging Report for each horizontal drainhole comprising the Stacked Lateral Well as required by Commission rules.

11. An operator may not file Form P-4 to transfer an individual surface location of a Stacked Lateral Well to another operator. P-4's filed to change the operator will only be accepted for the Record Well if accompanied by a separate P-4 for each surface location of the Stacked Lateral Well.

RULE 4a: Should an oil well be classified in the West Park (Granite Wash) Field, the gas field shall be classified as associated-prorated. The daily allowable production of gas from individual wells completed in the subject field shall be determined by allocating the allowable production, after deductions have been made for wells which are incapable of producing their gas allowables, among the individual wells in the following manner:

- a. FIVE percent (5%) of the total field allowable shall be allocated equally among the individual proratable wells producing from this field.
- b. NINETY FIVE percent (95%) of the total field allowable shall be allocated among the individual wells in the proportion that the deliverability of such well, as evidenced by the most recent G-10 test filed with the Railroad Commission bears to the summation of the deliverability of all proratable wells producing from this field.

The allocation formula in the West Park (Granite Wash) Field remains suspended. The allocation formula may be reinstated administratively, in accordance with Commission rules, if the market demand for gas in the West Park (Granite Wash) Field drops below 100% of deliverability.

Rule 4b: The maximum daily oil allowable for each well in the subject field shall be applicable yardstick allowable, and the actual allowable for an individual well shall be determined by the sum total of the two following values:

- a. Each well shall be assigned an allowable equal to its potential based on the most recent well test filed with the Commission multiplied by NINETY FIVE (95)%, provided that this value shall not exceed the applicable yardstick allowable multiplied by NINETY FIVE (95)%.

- b. Each well shall be assigned an allowable equal to FIVE (5)% of the maximum daily oil allowable above.

Done this 23rd day of September, 2008.

RAILROAD COMMISSION OF TEXAS

**(Order approved and signatures affixed
by OGC Unprotected Master Order
dated September 23, 2008)**