

**RAILROAD COMMISSION OF TEXAS
HEARINGS DIVISION**

**OIL AND GAS DOCKET
NO. 8A-0296051**

**IN THE BRAHANEY FIELD,
YOAKUM COUNTY, TEXAS**

ORDER NUNC PRO TUNC

**AMENDING FIELD RULES FOR
THE BRAHANEY FIELD,
YOAKUM COUNTY, TEXAS**

In conference at its office in Austin, Texas, The Railroad Commission of Texas took up for consideration its Final Order entered on July 14th, 2015, the matter amending field rules for the Brahaney Field, Yoakum County, Texas. The Commission finds that the final order omitted the Applicants request that no proration unit plats or form P-15 be required in the Brahaney Field. The Commission also omitted from the applicants request language regarding Non-Perforation Zones (NPZs).

Accordingly, it is **ORDERED** that the Final Order in Docket No. 8A-0296051 be, and the same is hereby, amended *nunc pro tunc* to include the language that no P-15 and proration unit plats shall be required. It is also amended to allow Non-Perforation Zones (NPZ's) for the Brahaney Field, Yoakum County, Texas. Furthermore, it is ordered that the Rule 3 requirement of requiring certified plats to be used for proration be deleted. The amended Field Rules for the Brahaney Field are set out in their entirety as follows:

RULE 1: The entire correlative interval from The correlative interval from 5,170 feet to 5,565 feet, as shown on the log of the Arco Oil & Gas Company Read# 1 Log, Yoakum County, Texas, shall designate the Field shall be designated as a single reservoir for proration purposes and be designated as the Brahaney Field.

RULE 2: No well for oil or gas shall hereafter be drilled nearer than THREE HUNDRED THIRTY (330) feet to any property line, lease line, or subdivision line. There is no minimum between well spacing limitation. The aforementioned distances in the above rule are minimum distances to allow an operator flexibility in locating a well, and the above spacing rule and the other rules to follow are for the purpose of permitting only one well to each drilling and proration unit in either field. Provided however, that the Commission will grant exceptions to permit drilling within shorter distances and drilling more wells than herein prescribed whenever the Commission shall have determined that such exceptions are necessary either to prevent waste or to prevent the confiscation of property. When exception to these rules is desired, application therefore shall be filed and will be acted upon in accordance with the provisions of Commission Statewide Rules 37 and 38, which applicable provisions of said rules are incorporated herein by reference.

In applying this rule, the general order of the Commission with relation to the subdivision of property shall be observed.

Provided, however, that for purposes of spacing for horizontal drainhole wells, the following shall apply:

- a. A take point in a horizontal drainhole well is any point along a horizontal drainhole where oil and/or gas can be produced from the reservoir/field interval. The first take point may be at a different location than the penetration point and the last take point may be at a location different than the terminus point.
- b. No horizontal drainhole well for oil or gas shall hereafter be drilled such that the first and last take points are nearer than TWO HUNDRED (200) feet to any property line, lease line or subdivision line.
- c. For each horizontal drainhole well, the distance perpendicular to such horizontal drainhole from any take point to any point on any property line, lease line or subdivision line shall be a minimum of THREE HUNDRED THIRTY (330) feet.

For the purpose of assigning additional acreage to a horizontal drainhole well pursuant to Statewide Rule 86, the distance from the first take point to the last take point in the horizontal drainhole shall be used in such determination, in lieu of the distance from penetration point to terminus.

If the applicant has represented in the drilling application that there will be one or more no perf zones or "NPZ's" (portions of the wellbore within the field interval without take points), then the as-drilled plat filed after completion of the well shall be certified by a person with knowledge of the facts pertinent to the application that the plat is accurately drawn to scale and correctly reflects all pertinent and required data. In addition to the standard required data, the certified plat shall include the as-drilled track of the wellbore, the location of each take point on the wellbore, the boundaries of any wholly or partially unleased tracts within a Rule 37 distance of the wellbore, and notations of the shortest distance from each wholly or partially unleased tract within a Rule 37 distance of the wellbore to the nearest take point on the wellbore.

A properly permitted horizontal drainhole will be considered to be in compliance with the spacing rules set forth herein if the as-drilled location falls within a rectangle established as follows:

- a. Two sides of the rectangle are parallel to the permitted drainhole and 47 feet on either side of the drainhole;
- b. The other two sides of the rectangle are perpendicular to the sides described in (a) above, with one of those sides passing through the first take point and the other side passing through the last take point.

Any take point of a horizontal drainhole outside of the described rectangle must conform to the permitted distance to the nearest property line, lease line or

subdivision line.

For any well permitted in this field, the penetration point need not be located on the same lease, pooled unit or unitized tract on which the well is permitted and may be located on an Offsite Tract. When the penetration point is located on such Offsite Tract, the applicant for such a drilling permit must give 21 days notice by certified mail, return receipt requested to the mineral owners of the Offsite Tract are (1) the designated operator; (2) all lessees of record for the Offsite Tract where there is no designated operator; and (3) all owners of unleased mineral interest where there is no designated operator or lessee. In providing such notice, applicant must provide the mineral owners of the Offsite Tract with a plat clearly depicting the projected path of the entire wellbore. In the event the applicant is unable, after due diligence, to locate the whereabouts of any person to whom notice is required by the rule, the applicant must publish notice of the application pursuant to the Commission's Rules of Practice and Procedure. If any mineral owner of the Offsite Tract objects to the location of the penetration point, the applicant may request a hearing to demonstrate the necessity of the location of the penetration point of the well to prevent waste or to protect correlative rights. Notice of Offsite Tract penetration is not required if (a) written waivers of objection are received from all mineral owners of the Offsite Tract; or, (b) the applicant is the only mineral owner of the Offsite Tract. To mitigate the potential for well collisions, applicant shall promptly provide copies of any directional surveys to the parties entitled to notice under this section, upon request.

RULE 3: The acreage assigned to an individual oil well for the purpose of allocating allowable oil production thereto shall be known as a proration unit. The standard drilling and proration units are established hereby to be FORTY(40) acres. No proration unit shall consist of more than FORTY(40) acres except as hereinafter provided. All proration units shall consist of continuous and contiguous acreage which can reasonably be considered to be productive of oil. No double assignment of acreage will be accepted.

If after the drilling of the last well on any lease and the assignment of acreage to each well thereon in accordance with the regulations of the Commission there remains an additional unassigned acreage of less than FORTY (40) acres, then and in such event the remaining unassigned acreage up to and including a total of TWENTY (20) acres may be assigned as tolerance acreage to the last well drilled on such lease or may be distributed among any group of wells located thereon, so long as the proration units resulting from the inclusion of such additional acreage meet the limitations prescribed by the Commission.

An operator, at his option, shall be permitted to form optional drilling units of TEN (10) acres. A proportional acreage allowable credit will be given for a well on a fractional proration unit. No Proration Unit Plats or Form P-15 shall be required.

RULE 4: The daily total field oil allowable as fixed by the Commission after deductions have been made for marginal wells, high gas-oil ratio wells and wells that are incapable of producing their allowables as determined hereby, shall be distributed among the remaining producing wells in the field on the following basis:

- (a) The daily allowable for each well, after said deductions have been made, shall be that proportion of seventy-five (75) percent of the daily field allowable which the acreage assigned to the well bears to the remaining acreage assigned to all the wells in the field.
- (b) The daily per well allowable for each well, after said deductions have been made, shall be determined by dividing twenty-five (25) percent of the total field daily allowable by the number of producing wells.

RULE 5: For oil and gas wells, Stacked Lateral Wells within the correlative interval for the field that are drilled from different wellbores may be considered a single well for regulatory purposes, at an operator's discretion, as provided below:

1. A horizontal drainhole well qualifies as a Stacked Lateral Well under the following conditions:
 - a. There are two or more horizontal drainhole wells on the same lease, or pooled unit within the correlative interval for the field;
 - b. Horizontal drainholes are drilled from different surface locations;
 - c. All take points of a Stacked Lateral Well's horizontal drainholes shall be within a rectangular area the width of which is SIX HUNDRED (600) feet, and the length of which is the distance from the two most distant take points;
 - d. There shall be no maximum or minimum distance limitations between horizontal drainholes of a Stacked Lateral Well in a vertical direction; and,
 - e. All horizontal drainholes must be tested independently and as a result have the same wellbore classification (i.e., gas or oil).
 - f. The first horizontal drainhole will be identified as the "Record Well." An operator may change the Record Well designation to another wellbore by filing the appropriate Commission forms.
2. A Stacked Lateral Well, including all surface locations and horizontal drainholes comprising such Stacked Lateral Well, shall be considered as a single well for density and allowable purposes.
 - a. The requirements of Statewide Rule 86(d)(4) shall not apply to stacked lateral wells.
 - b. For the purpose of assigning additional acreage to the Stacked Lateral Well pursuant to Field Rule 3 or Statewide Rule 86 as applicable, the horizontal drainhole displacement shall be calculated based on the distance from the first take point to the last take point in the horizontal drainhole for the Record Well, regardless of the horizontal drainhole displacement of other

horizontal drainholes of the Stacked Lateral Well.

3. Each surface location of a Stacked Lateral Well must be permitted separately and assigned an API number. In permitting a Stacked Lateral Well, the operator shall identify each surface location of such well as a Stacked Lateral Well in the on the Form W-1 drilling permit application. The operator shall also identify on the plat any other existing, or applied for, horizontal drainholes comprising the Stacked Lateral Well being permitted.
4. To be a regular location, each horizontal drainhole of a Stacked Lateral Well must comply with (i) the field's minimum spacing distance as to any lease, pooled unit or property line, and (ii) the field's minimum between well spacing distance as to any different well, including all horizontal drainholes of any other Stacked Lateral Well, on the same lease or pooled unit in the field. Operators may seek exceptions to Rules 37 and 38 for Stacked Lateral Wells in accordance with the Commission's rules, or any applicable rule for this field.
5. Operators shall file separate completion forms for each surface location of the Stacked Lateral Well. Operators shall also file a certified as-drilled location plat for each surface location of a Stacked Lateral Well showing each horizontal drainhole from that surface location, confirming the well's qualification as a Stacked Lateral Well and showing the maximum distances in a horizontal direction between each horizontal drainhole of the Stacked Lateral Well.
6. In addition to the Record Well, each surface location of a Stacked Lateral Well will be listed on the proration schedule, but no allowable shall be assigned for an individual surface location. Each surface location of a Stacked Lateral Well shall be required to have a separate G-10 or W-10 test and the sum of all horizontal drainhole test rates shall be reported as the test rate for the Record Well.
7. Operators shall report all production from horizontal drainholes included as a Stacked Lateral Well on Form PR to the Record Well. Production reported for a Record Well is the total production from the horizontal drainholes comprising the Stacked Lateral Well. Operators shall measure the production from each surface location of a Stacked Lateral Well. Operators may measure full well stream with the measurement adjusted for the allocation of condensate based on the gas to liquid ratio established by the most recent G-10 well test rate for that surface location. The gas and condensate production will be identified by individual API number and recorded and reported on the "Supplementary Attachment to Form PR".
8. Operators shall file an individual Form W-3A Notice of Intention to Plug and Abandon and Form W-3 Well Plugging Report for each horizontal drainhole comprising the Stacked Lateral Well as required by Commission rules.

9. An operator may not file Form P-4 to transfer an individual surface location of a Stacked Lateral Well to another operator. P-4's filed to change the operator will only be accepted for the Record Well if accompanied by a separate P-4 for each surface location of the Stacked Lateral Well.

Done this 25th day of April 2017.

**RAILROAD COMMISSION OF
TEXAS**

**(Order approved and signatures affixed
by Hearings Divisions' Unprotected
Master Order dated April 25, 2017)**